

Product Data Sheet

647-(1)-04/14



Makers of Fine Paint Since 1962

ISSUED: 22 April 2014

Page 1 of 2

647 Danish Oil Exterior

USE



THINNER/CLEAN



Mineral
Turpentine

APPLICATION



RE-COAT



8 - 12 Hrs

HAZARD



647 Danish Oil Exterior has a hand polished, low-lustre appearance. It is a penetrating, resin-based oil finish, for use on interior and exterior timbers. It is hard wearing, abrasion, heat and moisture resistant.

USES: 647 Danish Oil Exterior may be used on windows, skirting, doors and furniture. It can be used as sealer in its own right or it may be used as a rejuvenator for previously coated surfaces. 647 Danish Oil Exterior is a resin based oil finish that gives a low lustre hand rubbed finish and contains powerful UV inhibitors and absorbers to extend exterior life. For an attractive appearance and added UV protection 647 Danish Oil Exterior is also available in a range of transparent colours.

SURFACE PREPARATION: Surface to be coated should be free from all waxes, oils or grease.

NEW TIMBER: New exterior timber should first be primed using 649 Deeptreat. Refer to the 649 Deeptreat data sheet for instructions on the use of 649 Deeptreat. 647 Danish Oil Exterior can be applied as a 2 - 3 coat system depending on the porosity of the timber. Apply 647 Danish Oil Exterior with a brush or lambskin pad and allow it to penetrate for approx 5 minutes. Then wipe off any excess with a clean soft lint free cloth and allow to dry. Repeat process 2 or 3 times. Do not allow 647 Danish Oil Exterior to dry on the surface prior to wiping off excess material.

PREVIOUSLY VARNISHED SURFACES: Lightly sand to a smooth surface, if required. Wipe area to be coated with mineral turpentine and allow to dry. One or two coats of 647 Danish Oil Exterior are usually sufficient for previously painted surfaces.

DRYING: 1st. coat is touch dry in 30 minutes at 25°C. Lower temperatures prolong drying times

RE-COAT TIME: 8 to 12 hours at 25°C. Lower temperatures prolong drying times.

THINNING: 647 Danish Oil Exterior is supplied ready for use and thinning is not required.

CLEAN UP: Mineral turpentine.

STAINING: 647 Danish Oil Exterior is available in a range of transparent exterior colours.

MAINTENANCE: Wash surfaces previously coated with 647 Danish Oil Exterior with mild detergent and water. Re-coat using 647 Danish Oil Exterior.

CAUTION: Due to the danger of combustion it is advisable to lay oily rags flat to dry (preferably outside) prior to disposal.

TOPLINE PAINT PTY LTD

Telephone: (08) 8384 1188

33 ALDERSHOT ROAD, LONSDALE, SOUTH AUSTRALIA 5160.

Fax: (08) 8326 1824

E-mail: admin@toplinepaint.com.au

Customers need to appreciate that as Topline Paint cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.





647 Danish Oil Exterior

PRECAUTIONS:

The following information is a general guide only. Industrial users (ie where the product is being used in the workplace) are legally required to have available a Material Safety Data Sheet on this product. If you are unsure if you have an MSDS on this product please contact Topline Paint and one will be provided.

Safety Directions: **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water or store in a sealable glass container.

First Aid Instructions: If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

Leaks, Spills and Disposal: To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. DO NOT pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

Fire: Use foam and breathing apparatus. Avoid breathing products of combustion.

Hazard: The coloured square at the top of page 1 is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (eg water based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes