

# Product Data Sheet

648-(1)-04/14



Makers of Fine Paint Since 1962

ISSUED: 22 April 2014

Page 1 of 2

## 648 Danish Oil Interior

### USE



### THINNER/CLEAN



Mineral  
Turpentine

### APPLICATION



### RE-COAT



6 - 8 Hrs

### HAZARD



*648 Danish Oil Interior has a hand polished, low-lustre appearance. It is a penetrating, resin-based oil finish, for use on interior timbers. It is hard wearing, abrasion, heat and moisture resistant.*

**USES:** 648 Danish Oil Interior may be used on windows, skirting, doors and furniture. It can be used as sealer in its own right or it may be used as a rejuvenator for previously coated surfaces. 648 Danish Oil Interior is not a pure oil finish. It has the look of an oiled finish and is applied like an oil finish, but dries like a polyurethane finish, with the durability, heat resistance and moisture resistance of polyurethane.

**SURFACE PREPARATION:** Surface to be coated should be free from all waxes, oils or grease.

**NEW SURFACES:** 648 Danish Oil Interior can be applied as a 2 - 3 coat system directly onto timber, or it can be applied over a sealer coat of Spescoat Clear-thane satin. New Timber should be sanded to a smooth surface.

**PREVIOUSLY VARNISHED SURFACES:** Lightly sand to a smooth surface, if required. Wipe area to be coated with mineral turpentine and allow to dry. One or two coats of 648 Danish Oil Interior are usually sufficient for previously painted surfaces.

**APPLICATION:** Apply 648 Danish Oil Interior with a brush, pad or soft, lint-free cloth and allow to penetrate for approx 5 minutes, then buff with a soft cloth. Allow to dry. Repeat process until desired finish is achieved. We normally recommend 2-3 coats for new timber and 1-2 coats for previously varnished/sealed surfaces. Do not allow 648 Danish Oil Interior to dry on the surface prior to buffing.

**DRYING:** 1st. coat is touch dry in 10 minutes at 25°C. Lower temperatures prolong drying times

**RE-COAT TIME:** 6 to 8 hours at 25°C. Lower temperatures prolong drying times.

**THINNING:** 648 Danish Oil Interior is supplied ready for use and thinning is not required.

**CLEAN UP:** Mineral turpentine.

**STAINING:** 648 Danish Oil Interior can be applied over most oil or spirit wood stains. Alternatively some concentrated additive stains can be mixed into 648 Danish Oil Interior.

**CAUTION:** Due to the danger of combustion it is advisable to lay oily rags flat to dry (preferably outside) prior to disposal.

TOPLINE PAINT PTY LTD

33 ALDERSHOT ROAD, LONSDALE, SOUTH AUSTRALIA 5160.

Telephone: (08) 8384 1188

Fax: (08) 8326 1824

E-mail: admin@toplinepaint.com.au

Customers need to appreciate that as Topline Paint cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.





## 648 Danish Oil Interior

### PRECAUTIONS:

*The following information is a general guide only. Industrial users (ie where the product is being used in the workplace) are legally required to have available a Material Safety Data Sheet on this product. If you are unsure if you have an MSDS on this product please contact Topline Paint and one will be provided.*

**Safety Directions:** **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water or store in a sealable glass container.

**First Aid Instructions:** If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

**Leaks, Spills and Disposal:** To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. **DO NOT** pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

**Fire:** Use foam and breathing apparatus. Avoid breathing products of combustion.

**Hazard:** The coloured square at the top of page 1 is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (eg water based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes