

# Product Data Sheet

825-(7)-04/14



Makers of Fine Paint Since 1962

ISSUED: 02 May 2014

Page 1 of 2

## 825 Superhide Undercoat

USE



THINNER/CLEAN



Turpentine

APPLICATION



RE-COAT



16 Hrs

HAZARD



*A high opacity, easy brushing undercoat suitable for both interior and exterior use. Superhide gives a high build, sands easily and possesses excellent "hold out" for succeeding coats of enamel. Superhide Undercoat is oil modified and contains Zinc Oxide, thereby providing a better mould resistance and durability.*

**USES:** As a general purpose undercoat over primed woodwork that is to be top coated with Premium Super Gloss or Velvet Satin Enamel. Also suitable for other surfaces such as hardboard, asbestos, cement and steel suitably sealed or primed.

**SURFACE PREPARATION:** Surfaces to be painted must be clean and dry. Degrease if required and sand any previously painted glossy areas with 100-200 grit sand paper. Wipe down with a damp cloth. Fill any cracks or nail holes with a suitable filler. Again sand and clean the surface.

**Brick, Masonry, Plaster, Fibrous Cement, Etc:** Highly porous surfaces, powdery and chalky surfaces and smooth plaster should be first primed/sealed with 962 Hi-Fix Primer. New plaster or concrete should be allowed to cure and dry for at least 40 days. If surface is alkaline, seal with 1 coat 962 Hi-Fix Primer before undercoating.

**Timber:** Prepare the surface as per the general instructions above. Exterior Timber should first be primed with 809 Pink Wood Primer.

**Steelwork:** Degrease thoroughly with T-3 Wax and Grease Remover. Treat rust areas with Keline Rust Converter and apply 2 coats Forminex 660 Epoxy Undercoat.

**Galvanised Steel, Zinalume:** Degrease thoroughly with T-3 Was and Grease Remover to remove oily and greasy material. Apply one coat of 812 Sama Galvguard. Scrape painted surfaces to remove all loose and flaking paint. Treat rust areas with Keline Rust Converter. Apply 1 coat of Forminex 660 Epoxy Undercoat to treated rust areas.

**APPLICATION:** Stir thoroughly until product is uniform. Apply by brush.

**THINNING:** Supplied ready for use. However, if required, thin sparingly with Mineral Turpentine.

**CLEAN UP:** Mineral Turpentine.

**DRYING:** Touch dry 3-4 hours. Hard dry to re-coat after overnight drying under normal conditions at 25°C.

**COLOUR:** White.

**FINISH:** Flat.

**COVERAGE:** Theoretical coverage is 13 - 15 m<sup>2</sup>/Litre.

**PACK SIZES:** 1 litre, 4 Litre.

**VEHICLE TYPE:** Alkyd.

**PIGMENT TYPE:** Titanium Dioxide, inert esters.

### FILM PROPERTIES:

Solvent Resistance	Fair.	Chemical Resistance	Fair.
Abrasion Resistance	Good.	Impact Resistance	Good.
Heat Resistance	Good up to 100°C.	Flexibility	Good.

TOPLINE PAINT PTY LTD

33 ALDERSHOT ROAD, LONSDALE, SOUTH AUSTRALIA 5160.

Telephone: (08) 8384 1188

Fax: (08) 8326 1824

E-mail: admin@toplinepaint.com.au

Customers need to appreciate that as Topline Paint cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.





## 825 Superhide Undercoat

### PRECAUTIONS:

*The following information is a general guide only. Industrial users (ie where the product is being used in the workplace) are legally required to have available a Material Safety Data Sheet on this product. If you are unsure if you have an MSDS on this product please contact Topline Paint and one will be provided.*

**Safety Directions:** **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water or store in a sealable glass container.

**First Aid Instructions:** If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

**Leaks, Spills and Disposal:** To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. DO NOT pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

**Fire:** Use foam and breathing apparatus. Avoid breathing products of combustion.

**Hazard:** The coloured square at the top of page 1 is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (eg water based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes