

Product Data Sheet

834-(1)-05/14



Makers of Fine Paint Since 1962

ISSUED: 02 May 2014

Page 1 of 2

834 EasyFlow Flat Plastic

USE




THINNER/CLEAN



Water

APPLICATION




RE-COAT



2 - 3 Hrs

HAZARD



MONOPACK

A water based, economical vinyl modified paint suitable for interior and exterior use on most types of surfaces. Easy Flo Flat Plastic features excellent durability and colour retention on exterior exposure. Easy to apply and dries quickly.

USES: On all interior and exterior surfaces where a tough, fast drying Flat finish is required. 834 Easyflow Flay Plastic is ideal for the use on kitchen, bathroom and laundry walls as resistance to cleaning and scrubbing is excellent. 834 Easyflow Flay Plastic is also suitable as a two coat finish for plaster, cement render, wall board, masonry, brickwork, fibro cement and finally over appropriately primed woodwork, galvanised iron and steel.

SURFACE PREPARATION:

New Timber – Interior: Sand smooth and apply 824 Acrylic Undercoat.

New Timber – Exterior: Sand smooth and apply 824 Acrylic Undercoat. Leave 24 hours before applying Landmark Flat. For badly weathered or degraded timber we recommend 809 Pink Wood Primer.

Galvanised Iron: Prime with 812 Galvguard.

Plaster board eg Gyprock: Fill surface imperfections and apply direct or over 824 Acrylic undercoat.

Solid Plaster, Fibro Cement, Brick, Masonry: Fill surface imperfections and apply 962 Hi Fix Primer

Previously Painted Surfaces: Remove all glossy and powdery surfaces by sanding. Spot prime bare areas with the appropriate primer.

APPLICATION: Stir thoroughly until product is uniform. Apply by brush, roller or airless spray equipment.

THINNING: 834 Easyflow Flay Plastic is ready for application by airless spray brush or roller. However, thinning with water by 10% is recommended for the first coat over absorbent surfaces.

CLEAN UP: Wash out brushes and equipment in water.

DRYING: 834 Easyflow Flay Plastic is touch dry in 30 minutes under normal conditions (25°C). Allow 2-3 hours before re-coat.

COLOUR: 834 Easyflow Flay Plastic is available in white and a full range of decorative pastel and deep shades.

FINISH: Flat.

COVERAGE: Theoretical coverage is 14-16 m²/Litre at 40 micrometres dry film thickness.

PACK SIZES: 4 Litre, 10 Litre, 20 Litre.

VEHICLE TYPE: Modified acrylic emulsion.

PIGMENT TYPE: Titanium Dioxide and inert fillers.

FILM PROPERTIES:

Solvent Resistance	Poor.	Chemical Resistance	Fair.
Abrasion Resistance	Fair.	Impact Resistance	Good.
Heat Resistance	Fair.	Flexibility	Good.

TOPLINE PAINT PTY LTD

Telephone: (08) 8384 1188

33 ALDERSHOT ROAD, LONSDALE, SOUTH AUSTRALIA 5160.

Fax: (08) 8326 1824

E-mail: admin@toplinepaint.com.au

Customers need to appreciate that as Topline Paint cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.





834 EasyFlow Flat Plastic

Other Notes: Do not apply 834 Easyflow Flay Plastic when the temperature is less than 10°C, above 30°C or above 85% Relative Humidity.

PRECAUTIONS:

The following information is a general guide only. Industrial users (ie where the product is being used in the workplace) are legally required to have available a Material Safety Data Sheet on this product. If you are unsure if you have an MSDS on this product please contact Topline Paint and one will be provided.

Safety Directions: **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water or store in a sealable glass container.

First Aid Instructions: If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

Leaks, Spills and Disposal: To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. DO NOT pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

Fire: Use foam and breathing apparatus. Avoid breathing products of combustion.

Hazard: The coloured square at the top of page 1 is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (eg water based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes