

# Product Data Sheet

525-(8)-01/18



Makers of Fine Paint Since 1962

ISSUED: 23 January 2018

Page 1 of 2

## 525 Ultracoat Enamel

### USE



### THINNER/CLEAN



F-200  
T-14

### APPLICATION



### RECOAT Min 24 Hrs



### HAZARD



*525 Ultracoat Enamel has been formulated to provide the highest durability possible from a quick drying enamel. It has extremely high gloss, fast through drying and exceptional durability under severest weather conditions.*

**USES:** 525 Ultracoat Enamel was developed specially for the use in the re-finishing of trailers, trucks, transport vehicles and as well as the painting of machinery and structures.

**SURFACE PREPARATION:** All surfaces should be clean, dry and free from oil and grease. Use 131 Superbond on bright and non-ferrous surfaces. Steel surfaces should be primed with suitable anti corrosive primers such as the 131 Superbond or 291 Satin Primer systems.

**APPLICATION:** Stir thoroughly until product is uniform. 525 Ultracoat Enamel is best suited to spray application. Apply a light tack coat paying special attention to edges and corners, allow a short flash time (5 minutes) and then apply one full coat. 525 Ultracoat Enamel may also be brushed on small areas such as handrails or pipes.

Conventional Spray: 1.5 mm to 2mm Fluid nozzle at an air pressure of 45 to 50 psi (300-350 kPa) is recommended. Thin approximately 30% with F-200 Reducer.

Airless Spray: Recommended Tip size is 11 to 13 thou. Thin approximately 10-15% with F-200 Reducer.

Electrostatic Spray: 525 Ultracoat Enamel can be sprayed electrostatically. Please contact Topline Paint.

Brush: When brushing, Mineral Turps may be used sparingly to increase flow.

In hot conditions replace F-200 with F-205 to slow drying, improve flow and prevent dry spray.

**CLEAN UP:** F-200 Reducer or T-14 Gunwash.

**DRYING:** Touch dry 3-5 hours. Hard dry after approximately 24 hours. Re-coat time minimum 24 hours at 25°C. Use caution not to apply 525 Ultracoat too thickly in one application. Films over 100µm will be significantly slower in drying. This is well over normal film thicknesses but care should be exercised in awkward areas on trailers, for example, where multiple coats of adjoining parts could result in some areas being of excessive film thickness.

**COLOUR:** Wide colour range and colour matching available.

**FINISH:** Full gloss.

**COVERAGE:** Theoretical coverage 10-12 m<sup>2</sup>/Litre at 35 micrometres dry film thickness.

**PACK SIZES:** 4 Litre, 20 Litre.

**VEHICLE TYPE:** Modified alkyd resin.

**PIGMENT TYPE:** Lightfast Automotive pigments appropriate to the particular colour.

### FILM PROPERTIES:

Solvent Resistance	Good.	Chemical Resistance	Good.
Abrasion Resistance	Good.	Impact Resistance	Very Good.
Heat Resistance	Satisfactory up to 100°C (dry).	Flexibility	Very Good.

### TOPLINE PAINT PTY LTD

Telephone: (08) 8384 1188

### 33 ALDERSHOT ROAD, LONSDALE, SOUTH AUSTRALIA 5160.

Fax: (08) 8326 1824

E-mail: admin@toplinepaint.com.au

Customers need to appreciate that as Topline Paint cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.





## 525 Ultracoat Enamel

### PRECAUTIONS:

*The following information is a general guide only. Industrial users (ie where the product is being used in the workplace) are legally required to have available a Safety Data Sheet on this product. If you are unsure if you have an SDS on this product please contact Topline Paint and one will be provided.*

**Safety Directions:** **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water or store in a sealable glass container.

**First Aid Instructions:** If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

**Leaks, Spills and Disposal:** To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. **DO NOT** pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

**Fire:** Use foam and breathing apparatus. Avoid breathing products of combustion.

**Hazard:** The coloured square at the top of page 1 is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (eg water based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes