

Product Data Sheet

643-(3)-02/18



Makers of Fine Paint Since 1962

ISSUED: 02 February 2018

Page 1 of 2

643 Ceramaglass

USE



THINNER/CLEAN



Methylated
Spirits

APPLICATION



RE-COAT



HAZARD



Ceramaglass is a single pack, clear, adhesion promoting, fast drying primer. Ceramaglass can be used on glass, ceramic tiles, porcelain, terrazzo, some plastics, laminates, vinyl & lino and vitreous enamel.

DESCRIPTION: Forminex Ceramaglass is a single pack, clear, adhesion promoting, fast drying primer. Ceramaglass can be used on glass, ceramic tiles, porcelain, terrazzo, some plastics, laminates, vinyl & lino and vitreous enamel.

USES: Ceramaglass is used on surfaces to which paint would not adhere. Glass, glazed ceramic or porcelain tiles would normally require strong abrasion or dangerous acid etching in order to provide a suitable key for the appropriate painting system to follow. CERAMAGLASS is simply wiped onto the cleaned surface and allowed to dry for 1 hour. This saves expensive labour costs as well eliminating the need to use strong acids for etching the surface. Ceramaglass can be over-coated with almost any paint system including two-pack urethanes and epoxies. Ceramaglass makes kitchen and bathroom makeovers simple.

PREPARATION: Surface must be thoroughly free of oil dirt, grease and soap residue etc. Rinse surface thoroughly after cleaning. Allow surface to dry before application of Ceramaglass .

NOTE: Do not open until ready for use. Protect against moisture contamination.

APPLICATION: Apply one coat sparingly by sponge or lint free cotton cloth.

COVERAGE: 40-80 m² per litre depending on porosity of surface.

WHEN TO PAINT: Ideal application temperature 15-30°C. Avoid painting in direct sunlight. Do not use if temperature is likely to drop below 10°C during curing period.

DRYING/RECOATING: Touch dry in 10 mins. Recoat with finishing system after 1 hour. Re-apply if left for more than 24 hrs.

THINNING: Thinning is not recommended as solvents may introduce moisture.

CLEAN UP: Clean equipment with Isopropyl alcohol or methylated spirits. Do not clean hands with solvents, use suitable hand cleaner.

TOPLINE PAINT PTY LTD

Telephone: (08) 8384 1188

33 ALDERSHOT ROAD, LONSDALE, SOUTH AUSTRALIA 5160.

Fax: (08) 8326 1824

E-mail: admin@toplinepaint.com.au

Customers need to appreciate that as Topline Paint cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.





643 Ceramaglass

PRECAUTIONS:

The following information is a general guide only. Industrial users (ie where the product is being used in the workplace) are legally required to have available a Safety Data Sheet on this product. If you are unsure if you have an SDS on this product please contact Topline Paint and one will be provided.

Safety Directions: **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water or store in a sealable glass container.

First Aid Instructions: If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

Leaks, Spills and Disposal: To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. DO NOT pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

Fire: Use foam and breathing apparatus. Avoid breathing products of combustion.

Hazard: The coloured square at the top of page 1 is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (eg water based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes