

Product Data Sheet

645-(1)-02/18




Makers of Fine Paint Since 1962

ISSUED: 16 February 2018

Page 1 of 2

645 Mop Top



645 Mop-Top is a mop on, wax free polish for use over timber finishes.

DESCRIPTION: 645 Mop-Top is a mop on, wax free polish for use over timber finishes such as 672 Tung Oil Sealer, 651 Floor-thane, 652 Floor Tuff and a variety of other timber and cork sealers. It can also be used to maintain sealed: slate, terracotta, concrete, ceramic tiles, and vinyl. It provides a durable scuff resistant surface that is easily maintained as necessary.

Application over new sealers: It is recommended that sealers such as 672 Tung Oil Sealer be allowed to cure for 4 weeks prior to the application of 645 Mop Top.

Application: Ensure surface is clean and dry. Apply one coat of 645 Mop Top with a clean damp mop or sponge. Apply in even slow strokes to avoid creating bubbles. Do **not** shake container before use. On very porous surfaces a second coat may be necessary.

Drying time: Touch dry in 10 – 20 minutes.

Re-coat time: 30-60 minutes. After a 24-hour drying period, 645 Mop Top may be machine buffed to 1000rpm

Maintenance cleaning: Wash floor with 684 Super Wash, or a PH neutral, ammonia free detergent. Ammonia based or alkaline detergents will act as a stripper for Mop-Top

Thinners: Thinning not recommended.

Clean up: Water

Stripping: If for any reason it is necessary to strip 645 Mop Top, an ammonia-based cleaner such as cloudy ammonia or an alkaline stripper is recommended.

Storage: Store in original container, securely closed, in cool dry place.

TOPLINE PAINT PTY LTD

Telephone: (08) 8384 1188

33 ALDERSHOT ROAD, LONSDALE, SOUTH AUSTRALIA 5160.

Fax: (08) 8326 1824

E-mail: admin@toplinepaint.com.au

Customers need to appreciate that as Topline Paint cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.





645 Mop Top

PRECAUTIONS:

The following information is a general guide only. Industrial users (ie where the product is being used in the workplace) are legally required to have available a Safety Data Sheet on this product. If you are unsure if you have an SDS on this product please contact Topline Paint and one will be provided.

Safety Directions: **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water or store in a sealable glass container.

First Aid Instructions: If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

Leaks, Spills and Disposal: To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. DO NOT pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

Fire: Use foam and breathing apparatus. Avoid breathing products of combustion.

Hazard: The coloured square at the top of page 1 is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (eg water based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes.