

Product Data Sheet

832-(4)-02/18



Makers of Fine Paint Since 1962

ISSUED: 23 February 2018

Page 1 of 2

832 Landmark Low Sheen

USE




THINNER/CLEAN



Water

APPLICATION



RE-COAT



2 Hrs

HAZARD



MONOPACK

832 Landmark Low Sheen is a water based, acrylic modified, low sheen paint for interior use on many types of surface. This Product features excellent flexibility, colour retention, scrub ability, washability and stain resistance. It is easy to apply and has excellent hiding.

USES: 832 Landmark Low Sheen is suitable for interior walls and ceilings. It is ideal where a lower sheen than a satin finish is required, but washability is still crucial. The low sheen finish tends to cover up surface imperfections and irregularities and provides a soft decorative finish.

SURFACE PREPARATION: Surfaces to be painted should be clean, dry and free from oil, grease and flakes. Old paint which is powdery, loose or flaking must be removed by scraping and sanding.

Powdery surfaces: Loosely adhering powdery surfaces require special treatment. Remove all kalsomine or powder by washing with a coarse rag or similar material, then apply one coat of 962 Hi-Fix Primer as per instructions.

Previously Painted Surfaces: Wash surface with sugar soap or equivalent to remove all dirt/grime before painting. Glossy surfaces should be lightly sanded and one coat of 824 Acrylic Undercoat applied before applying 832 Landmark Low Sheen.

Paperfaced Plasterboard: eg Gyprock: Fill any imperfections with appropriate filler, sand and dust down. Apply one coat of 824 Acrylic Oil Undercoat.

Masonry, Brick, Fibro, Render or Concrete: Fill any imperfections with appropriate filler, sand and dust down. Apply one coat of 824 Acrylic Oil Undercoat. It may be helpful to damp down highly absorbent walls prior to painting. **Beware:** Some Fibro Sheeting may be asbestos cement – do not cut, sand or drill this material as the fibres and dust are dangerous. Seek professional advice regarding the handling of this material.

APPLICATION: Brush, Roller or Airless Spray.

THINNING: Ready for Use. Product may be thinned up to 10% to aid penetration into absorbent substrates.

CLEAN UP: Water

DRYING: Touch dry 30 minutes and dry to recoat in 2 hours @ 25°C. Maximum scrub and stain resistance will not be achieved for 3 – 7 days.

COLOUR: Wide colour range available.

FINISH: Low Sheen

COVERAGE: Theoretical coverage 14-16 m²/Litre at 30 microns dry film thickness.

PACK SIZES:

1 Litre, 4 Litre, 10 Lt, 20 Lt (some colours only)

VEHICLE TYPE: Acrylic Emulsion

FILM PROPERTIES:

Solvent Resistance	Fair.	Chemical Resistance	Good.
Abrasion Resistance	Excellent.	Impact Resistance	Good.
Heat Resistance	Good up to 100°C.	Flexibility	Good.

TOPLINE PAINT PTY LTD

33 ALDERSHOT ROAD, LONSDALE, SOUTH AUSTRALIA 5160.

Telephone: (08) 8384 1188

Fax: (08) 8326 1824

E-mail: admin@toplinepaint.com.au

Customers need to appreciate that as Topline Paint cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.





832 Landmark Low Sheen

PRECAUTIONS:

The following information is a general guide only. Industrial users (ie where the product is being used in the workplace) are legally required to have available a Safety Data Sheet on this product. If you are unsure if you have an SDS on this product please contact Topline Paint and one will be provided.

Safety Directions: **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water or store in a sealable glass container.

First Aid Instructions: If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

Leaks, Spills and Disposal: To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. **DO NOT** pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

Fire: Use foam and breathing apparatus. Avoid breathing products of combustion.

Hazard: The coloured square at the top of page 1 is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (eg water based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes