








# 862 Sports Floor Finish Solvent Based

USE	THINNER/CLEAN	APPLICATION	RECOAT	HAZARD
	 Mineral Turps		6 - 8 Hrs 	 <b>MONOPACK</b>

*Monopack Sports Floor Solvent Based Finish is recommended as a tough solvent based clear gloss urethane finish on strip timber. It is suitable for both new floors and for re-coating.*

**PRINCIPAL USES:** MONOPACK Sports Floor Solvent Based Finish is recommended as a tough solvent based clear gloss urethane finish on strip timber. It is suitable for both new floors and for re-coating.

**SURFACE PREPARATION:** For re-coating of previously coated floors it is essential that all contaminants such as grease, oils, fats, cleaning chemicals etc. be completely removed by machine wet scrubbing using a 1:3 solution of Monopack Floorstrip in hot water. Do not re-coat with Monopack Sports Floor Solvent Based Finish if a wax, acrylic, or a silicone based polish has been used previously on the floor.

After pre-cleaning, lightly abrade with 220 grit screen backs, followed by thorough vacuuming. If doubts exist regarding the suitability of the surface for re-coating, carry out an adhesion test. Refer Information Sheet Application of Monopack Sports Floor Finish.

**THINNING:** Not normally required, however the product may be thinned up to 5% with Mineral Turpentine for the first coat on bare timber if desired.

**CLEAN UP:** Clean all equipment with Mineral Turps

**PACKAGING:** 20 Lt

**DRYING:** Recommended drying time before light foot traffic is four days. Full cure takes seven days.

**COVERAGE:** Coverage depends on thickness of application, type of timber, and timber absorbency. Hardwoods: 10 – 12 m<sup>2</sup>/lt



# 862 Sports Floor Finish Solvent Based

**APPLICATION GUIDELINES:** For ease of application and optimum drying rates, apply at temperatures between 15° and 30° Celsius. Apply with a roller, using a 6-10mm pile cover. Or apply using a weighted bar applicator fitted with a woven fabric cover. For new floors or complete re-sands, use a minimum of three coats allowing 24 hours between coats. (Allow 48 hours to dry in cold weather) Light sand between coats with 220 grit medium. If the coating does not sand to a powder, leave another 24 hours. (Some timbers exude oils and antioxidants which retard the curing process)

**PRECAUTIONS:** The following information is a general guide only. Industrial users (i.e. where the product is being used in the workplace) are legally required to have available a Safety Data Sheet on this product. If you are unsure if you have an SDS on this product please contact Topline Paint and one will be provided.

**Safety Directions:** **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition, immerse in water or store in a sealable glass container.

**First Aid Instructions:** If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

**Leaks, Spills and Disposal:** To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. DO NOT pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

**Fire:** Use foam and breathing apparatus. Avoid breathing products of combustion.

**Hazard:** The coloured square at the top of page 1 is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (e.g. water-based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes