

# Product Data Sheet

874-(3)-02/18




Makers of Fine Paint Since 1962

ISSUED: 23 February 2018

Page 1 of 2

## 874 Tung Oil Sealer



*Monopack Tung Oil Sealer is a single pack, clear, oil based surface sealer that will enhance the natural timber appearance of floors.*

**PRINCIPAL USES:** Monopack Tung Oil Sealer is a single pack, clear, oil based surface sealer that will enhance the natural timber appearance of floors. It provides a subdued low sheen finish that is ideal for domestic situations. It is also hard wearing and mar resistant.

**SURFACE PREPARATION:** New and worn floors require sanding to a fine finish, followed by thorough vacuum to remove all dust.

**APPLICATION:** Stir thoroughly before use. Apply with a short nap (6-10mm) roller. For ease of application and optimum drying rate, apply only at temperatures between 10 and 30°C. Apply two or three coats and allow overnight dry between coats. Sand between coats with 220 grit screenbacks.

**THINNING:** Thinning is not normally required, but if desired, use up to 5% Monopack Reducer Thinner.

**PACKAGING:** 10 Litre, 20 Litre.

**COLOUR:** Clear.

**FINISH:** Subdued Gloss

**COVERAGE:** Theoretical coverage is 10-14m<sup>2</sup> per Litre per coat, depending on the absorbency of the timber.

**DRYING:** Dry after 18 hours at a room temperature of 25°C and 40% humidity. Allow four days drying time before permitting light foot traffic. Avoid stiletto heels at all times.

**SAFETY DIRECTIONS:** Flammable Liquid 3, Packaging Group II, UN No. 1263, Paint. Hazchem 3(Y) E.

**TOPLINE PAINT PTY LTD**

Telephone: (08) 8384 1188

**33 ALDRSHOT ROAD, LONSDALE, SOUTH AUSTRALIA 5160.**

Fax: (08) 8326 1824

E-mail: admin@toplinepaint.com.au

Customers need to appreciate that as Topline Paint cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.





## 874 Tung Oil Sealer

### PRECAUTIONS:

*The following information is a general guide only. Industrial users (ie where the product is being used in the workplace) are legally required to have available a Safety Data Sheet on this product. If you are unsure if you have an SDS on this product please contact Topline Paint and one will be provided.*

**Safety Directions:** **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water or store in a sealable glass container.

**First Aid Instructions:** If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

**Leaks, Spills and Disposal:** To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. DO NOT pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

**Fire:** Use foam and breathing apparatus. Avoid breathing products of combustion.

**Hazard:** The coloured square at the top of page 1 is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (eg water based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes