

Safety Data Sheet



Makers of Fine Paint Since 1962

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: **691 Pave Seal**
Recommended Use: Water Based Paint.
Supplier: Topline Paint Pty Ltd t/as Shipway Spescoat
ABN: 65 007 626 191
Street Address: 33 Aldershot Road
Lonsdale SA 5160
Australia
Telephone Number: +61 8 8384 1188
Facsimile: +61 8 8326 1824
Email: info@toplinepaint.com.au




2. HAZARDS IDENTIFICATION

This material is non-hazardous according to criteria of Safe Work Australia; NON HAZARDOUS SUBSTANCE.

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; NOT DANGEROUS GOODS.

Risk Phrases: None.
Safety Phrases: None.
Poisons Schedule: None allocated.



3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
Triethoxy (s,4,4-trimethylpentyl) silane	35435-21-3	1-9%	
Alpha-i-tridecyl-omega-hydroxypolyglycoether	9043-30-5	<1.0%	-
3-(2-Aminoethylamino) propyl trimethoxysilane	1760-24-3	<1.0%	
2-Butoxyethyl acetate	112-07-2	<1.0%	
Tridecanol ethoxylate, branched with 3-5 EO	69011-36-5	<1.0%	
Tridecanoethoxylate, branched	69011-36-5	<1.0%	

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre 131 126 or a doctor.

Inhalation: Remove the source of contamination or move the victim to fresh air. Ensure airways are clear and have a qualified person give oxygen through facemask if breathing is difficult. Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected areas with copious amounts of soap and water. Ensure contaminated clothing is washed before re-use or discard. Seek medical attention.

Eye Contact: If contact with the eye(s) occur, wash with copious amounts of water, holding eyelid(s) open. Take care not to rinse contaminated water into the non-affected eye. If irritation develops, seek medical attention.

Ingestion: DO NOT induce vomiting. Immediately wash mouth out with water. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

Not Classed as flammable. If involved in a fire, it may emit noxious and toxic fumes.

Extinguishing media: Use extinguishing media suitable for surrounding area.

Special precautions: Wear breathing apparatus plus protective gloves for fire only. Prevent, by any means available, spillage from entering drains or watercourses. Cool fire exposed containers with water spray from a protected location. DO NOT approach containers suspected to be hot. Use fire fighting procedures suitable for surrounding area.

Fire/Explosion Hazard: This material is not readily combustible under normal conditions. However, it will break down under fire conditions and the organic component may burn. Not considered to be a significant fire risk. Heat may cause expansion or decomposition with violent rupture of containers. Decomposes on heating and may produce toxic fumes of carbon monoxide. May emit acrid smoke.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures: Remove all sources of ignition. Increase ventilation. Evacuate all unnecessary personnel. Wear full protective equipment and clothing to minimise exposure. If possible contain the spill.

Methods and materials for containment and clean up: Place inert, non combustible, absorbent material onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container. If large quantities of this material enter the waterways contact the Environmental Protection Authority, or your local Waste Management Authority.

7. HANDLING AND STORAGE

Conditions for safe storage: Store in original containers. Keep containers securely sealed. Store in a cool, dry, well ventilated area. DO NOT allow freeze. Store away from incompatible materials.

Precautions for safe handling: Limit all unnecessary personal contact. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be cleaned separately. Use in a well ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits: No exposure standards have been established for this material by the National Occupational Health And Safety Commission (NOHSC). However, all exposure should be kept to the least possible levels as over-exposure to any chemical may result in enhancement of pre-existing adverse medical conditions and/or allergic reactions. Exposure standards for individual constituents are listed above.

Engineering controls: Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Keep containers closed when not in use. Vapour heavier than air – prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is recommended.

Personal Protective Equipment:

Respiratory Protection: Avoid breathing of vapours/mists. Where ventilation is inadequate and vapours/mists are generated, the use of an approved respirator with filter complying with AS/NZS 1715 and AS/NZS 1716 is recommended; however final choice of appropriate breathing protection is dependant upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715- Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716- Respiratory Protective Devices.

Hand Protection: General protective gloves recommended as appropriate. Final choice of appropriate glove type will vary according to individual circumstances, including methods of handling or engineering controls as determined by appropriate risk assessments. Refer to AS/NZS 2161 Occupational protective gloves- Selection, use and maintenance.

Eye Protection: Chemical safety glasses or face shield recommended as appropriate. Final choice of appropriate eye/face protection will vary according to individual circumstances including methods of handling or engineering controls as determined by appropriate risk assessments. Eye protection should conform to Australian/New Zealand Standard AS/NZS 1337- Eye Protectors for Industrial Applications.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Coloured liquid
Decomposition Temperature	Not available
Melting Point	Not available
Boiling Point	>95°C at 1014 hPa
Solubility in Water	Completely miscible
Specific Gravity	1.0 g/cm ³ @ 25 °C, at 1014 hPa
pH Value	6 at 25 °C
Vapour Pressure	Approx. 25 hPa at 20 °C
Viscosity	Not available
Flash Point	>100°C (ISO 2719)
Flammability	Non Flammable
Ignition Temperature	Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions of storage and handling.

Conditions to avoid: Strong oxidising agents

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Toxicological tests

Acute toxicity (LD50/LC50-values relevant to classification):

Exposition	Value/value range	Species	Source
by inhalation	5.4 mg/1/4h (spray/dust)	rat	test report

Specific symptoms in animal test:

Acute inhalation: A dilution of 5% actives in water has been tested.

Further toxicological information:

Aerosol mist must not be inhaled, as lung damage can be expected. Product(s) of hydrolysis: According to literature, ethanol (67-17-5) irritates the mucous membranes, slightly irritates the skin, degreases the skin, is narcotic and may cause liver damage.

Ingestion: This liquid is discomforting and may be harmful if swallowed. Ingestion may result in nausea, abdominal irritation, pain and vomiting.

Eye contact: The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflammation, ulceration.

Skin contact: The liquid is mildly discomforting to the skin and is capable of causing skin reactions which may lead to dermatitis.

Long Term Effects: Prolonged and repeated skin contact may cause drying with cracking, irritation and possible dermatitis following. As with any chemical product, contact with unprotected bare skin: inhalation of vapour, mist or dust in work place atmosphere: or ingestion in any form, should be avoided by observing good occupational work practice.

Toxicological Data: No toxicology data is available for this product.

12. ECOLOGICAL INFORMATION

No Data available.

13. DISPOSAL CONSIDERATIONS

Disposal methods: Refer to Waste Management Authority. Dispose of material through a licensed waste contractor.

14. TRANSPORT INFORMATION

Road and Rail Transport Not Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; NOT DANGEROUS GOODS.

UN No: Non allocated

Class-primary: Non allocated

Packing Group: Non allocated

Proper Shipping Name: Non allocated

Hazchem Code: Non allocated

15. REGULATORY INFORMATION

Classification: This material is non-hazardous according to criteria of Safe Work Australia; NON HAZARDOUS SUBSTANCE.

Hazard Category: None allocated

Risk Phrase(s): None allocated

Safety Phrase(s): None allocated

Poisons Schedule: None allocated

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

This MSDS summarizes to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Topline Paint Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material. Persons dealing with the products to which this information refers do so entirely at their own risk. Topline Paint Pty. Ltd. will accept no responsibility what so ever for the consequences of the use or misuse of this product.